

ARTICLE: JORA-CLEAN PLASTIC CLEANER JCK 960
SYSTEM: PLASTIC CLEANER

PRODUCT PROPERTIES	SCOPE OF APPLICATION
<p>Careline are care and cleaning products. They are not only used for the cleaning of your surface, but also for a lasting preservation of value in all areas.</p> <p>For cleaning plastic surfaces and plastic edges.</p> <p>JORA -CLEAN PLASTIC CLEANER JCK 960 is used for reliable, mild, streak-free cleaning and degreasing of plastic surfaces and plastic edges.</p> <p>JCK 960 effectively removes adhesive residues or glue remnants, traces of adhesive strips as well as ballpoint pen, pencil and felt-tip marks.</p>	<p>JORA CLEAN PLASTIC CLEANER can be used to remove labels from almost all plastic surfaces such as ABS, melamine, PE, PP or PVC.</p> <p>The plastic cleaner is suitable for cleaning:</p> <ul style="list-style-type: none"> ▪ Plastic-coated furniture ▪ ABS, melamine ▪ PE, PP, PVC
TECHNICAL DATA	APPLICATION
<ul style="list-style-type: none"> ▪ Color: transparent ▪ Viscosity: 10-12 s (DIN 53211/ 4mm) 	<p>Soak a clean cloth with plastic cleaner JCK 960 and wipe over the contaminated surface. For spray bottles, spray the plastic cleaner JCK 960 directly onto the contamination and wipe the surfaces to be cleaned with a clean cloth.</p>
STORAGE	SPECIAL GUIDANCE
<p>Storage:</p> <p>Store material in a tightly closed container</p> <p>Don't store below 5°C.</p> <p>Shelf-Life:</p> <p>12 months (when stored in the original unopened containers)</p>	<ul style="list-style-type: none"> ▪ Before using the cleaner, the surface to be cleaned should always be tested for compatibility on a concealed test site or a test surface. ▪ Protect from sunlight. ▪ The material may become electrostatically charged. It must therefore be kept away from ignition sources and measures taken against electrostatic charges. ▪ Do not inhale vapours or use in well ventilated rooms. ▪ The usual precautions for handling chemicals must be observed. ▪ Do not allow to enter drains or waters. ▪ Keep out of reach of children. ▪ In the case of parquet which has been sealed on site, initial care must only be applied after approx. 15 days (after complete hardening of the varnish).

Item No.: JCK 960

Safety guidance:

The information in this technical data sheet is based on the current knowledge and experience of PLANTAG Coatings GmbH. The product processor is not exempted from its own testing and testing of the products with regard to the intended use as well as the wealth of possible influences during processing and application. Existing laws and regulations are to be observed by the recipient of our products in their own responsibility. Labeling in accordance with the Ordinance on Hazardous Substances and Transport Law can be found in the safety data sheet. A legally binding assurance of certain properties or suitability for a specific purpose cannot be derived from our information. Recommendations deviating from the information in our technical data sheets are only binding for us if they have been confirmed in writing. Our terms and conditions are an integral part of this technical information sheet [Nov-19]

PLANTAG Coatings GmbH
 Plantagenweg 34-38
 32758 Detmold
 GERMANY
 Fon: +49 5231 6002 661
 Fax: +49 5231 6002 9661
 E-Mail: info@jordanlacke.de

JORDAN LACKE – a trademark of PLANTAG Coatings GmbH