


ARTICLE: AQUA-CLEAN
ITEM-NO.: JZ9460-0-001
SYSTEM: Cleaning agent for water-based lacquers

PRODUCT PROPERTIES	SCOPE OF APPLICATION
Aqua-Clean JZ9460-0-001 is a cleaning agent for water-based lacquers especially for spraying equipment. The cleaner is suitable for the thorough removal of water-based lacquer from spray guns.	<p>Suitable for cleaning:</p> <ul style="list-style-type: none"> Paint-carrying pipes and ducts For rinsing out pigment deposits <p>The product is used for cleaning:</p> <ul style="list-style-type: none"> Automatic spray guns Manual spraying equipment
TECHNICAL DATA	STORAGE
<p>The cleaner is most effective when freshly mixed with water.</p> <p>The best results are achieved when the cleaner is diluted with clear water at a mixing ratio of 1:4 to 1:10. For this reason, it is not recommended to use the cleaner pure.</p>	 <p>Store tightly closed in a cool and dry place</p> <p>Shelf-Life: 12 months (when stored in the original unopened containers)</p>
SPECIAL GUIDANCE	
<ul style="list-style-type: none"> Do not mix cleaner with other cleaners! Do not add any solvents to the mixture! The cleaner is slightly corrosive to non-ferrous metals and aluminium. Systems must not be exposed to it for long periods of time. After cleaning, pure water or other suitable agents should be rinsed into the pipes. Cleaner residues must be removed thoroughly with water. 	

Item-No.: JZ9460-0-001

Safety guidance:

The information in this technical data sheet is based on the current knowledge and experience of PLANTAG Coatings GmbH. The product processor is not exempted from its own testing and testing of the products with regard to the intended use as well as the wealth of possible influences during processing and application. Existing laws and regulations are to be observed by the recipient of our products in their own responsibility. Labeling in accordance with the Ordinance on Hazardous Substances and Transport Law can be found in the safety data sheet. A legally binding assurance of certain properties or suitability for a specific purpose cannot be derived from our information. Recommendations deviating from the information in our technical data sheets are only binding for us if they have been confirmed in writing. Our terms and conditions are an integral part of this technical information sheet [Jun 25]

PLANTAG Coatings GmbH
Ohmstraße 8
32758 Detmold
GERMANY
Fon: +49 5231 6002 661
Fax: +49 5231 6002 9661
E-Mail: info@jordanlacke.de

JORDAN LACKE – a trademark of PLANTAG Coatings GmbH