# **TECHNICAL DATA SHEET**



ARTICLE: CLASSIC-COLOR-CONCENTRATE

ITEM-NO.: JC1900-X

SYSTEM: Colour Concentrate

## PRODUCT PROPERTIES

CLASSIC-COLOR-CONCENTRATES are lightfast, transparent colour solutions so that you can mix the colours based on our solvent-based clear lacquers

They are characterized by:

- high colour concentration
- easy to blend

Colour:

# **COPE OF APPLICATION**

Colour concentrates for colouring clear lacquers

## **TECHNICAL DATA**

JC1900-01001, yellow JC1900-01002, orange JC1900-03001, red JC1900-03002, rubin JC1900-051001, blue JC1900-06001, green JC1900-08001, brown JC1900-09001, black

The concentrates can be mixed with

each other.

Dosing: Addition quantity on clear coat

approx. 0.5 - 1 %.

Temperature: See processing temperature for the

corresponding coating materia!

# STORAGE erial in a tightly o

Store material in a tightly closed container.

Shelf-Life: 12 months

(when stored in the original unopened containers)

# **CLEANING**

Clean tools immediately after use with

UNI-CLEAN JT1803-0-001,

**₩**₩₩

- NITRO-THINNER JT1415-0-001,
- DD-THINNER JT1244-0-001

## **APPLICATION**

- CLASSIC-COLOR-CONCENTRATES are usually added in quantities of approx. 0.5 to 1 % to the corresponding topcoats or finishing lacquers.
- If possible, the coloured material should be sprayed onto already pre-primed and properly intermediately sanded surfaces to obtain a uniformly coloure surface.
- The material is applied by spraying. This must be done completely evenly - especially on larger surfaces - to avoid "streaks" or "cloud formation".

## **SPECIAL GUIDANCE**

- It is advisable to make a reference sample before starting the spraying work with the coloured materials in order to ensure the correctness of the colour tone!
- In general, the colour tone depends on the additional quantity of CLASSIC-COLOR-CONCENTRATE as well as on the application quantity and the type of wood or the inherent colour of the wood

## Safety guidance:

The information in this technical data sheet is based on the current knowledge and experience of PLANTAG Coatings GmbH. The product processor is not exempted from its own testing and testing of the products with regard to the intended use as well as the wealth of possible influences during processing and application. Existing laws and regulations are to be observed by the recipient of our products in their own responsibility. Labeling in accordance with the Ordinance on Hazardous Substances and Transport Law can be found in the safety data sheet. A legally binding assurance of certain properties or suitability for a specific purpose cannot be derived from our information. Recommendations deviating from the information in our technical data sheets are only binding for us if they have been confirmed in writing. Our terms and conditions are an integral part of this technical information sheet. [Jun-25]

PLANTAG Coatings GmbH Ohmstraße 8 32758 Detmold

DEUTSCHLAND
Fon: +49 5231 6002 66'
Fax: +49 5231 6002 966'
F.Mail: info@iordanlacke

JORDAN LACKE – – a trademark of PLANTAG Coatings