

TECHNICAL DATA SHEET

ARTICLE: JORA-CARE-BASIC-CLEANER
ITEM NO.: JZ7920-0-001
SYSTEM: INTENSIVE CLEANER

PRODUCT PROPERTIES		SCOPE OF APPLICATION	
<p>Careline are care and cleaning products. They are not only used for the cleaning of your surface, but also for a lasting preservation of value in all areas.</p> <p>Highly effective cleaning agent for oiled and lacquered surfaces with high susceptibility to dirt.</p> <p>Suitable for removing old layers of care products and stubborn dirt. For oiled surfaces please use JORA-CARE-MAINTENANCE-AGENT as cleaner.</p>		<p>For removing heavy soiling and old layers of care products.</p> <ul style="list-style-type: none"> Parquet flooring Laminate PVC flooring 	
TECHNICAL DATA		APPLICATION	
<ul style="list-style-type: none"> Color: blue, transparent Consumption: approx. 1 l / 20 m² 		<p>Basic cleaning: Spray the JORA-CARE-BASIC-CLEANER onto the surface, spread evenly and thinly and allow to act briefly. Then wipe off with an absorbent cloth or sponge. The surface treated with this BASIC-CLEANER should always be wiped with water after the treatment and then be allowed to dry. Afterwards, normal care can be resumed. Working too wet can cause the fibers to swell and/or the wood to discolor. Adjoining surfaces must be protected from the effects of the BASIC-CLEANER.</p> <p>Professional cleaning: For large surfaces a single disc machine with cleaning pad in beige is used. Such surfaces are efficiently processed in sections by two persons. The one person removes the cleaning agent film with a surface wiper before it dries.</p>	
STORAGE		SPECIAL GUIDANCE	
<p>Storage:</p> <p>Store material in a tightly closed container</p> <p>Don't store below 5°C.</p> <p>Shelf-Life:</p> <p>12 months (when stored in the original unopened containers)</p>		<ul style="list-style-type: none"> Shake well before use! Before using the cleaner, the surface to be cleaned should always be tested for compatibility on a concealed test site or a test surface. The usual precautions for handling chemicals must be observed. Do not allow to enter drains or waters. Keep out of reach of children. In the case of parquet which has been sealed on site, initial care must only be applied after approx. 15 days (after complete hardening of the varnish). JORA-CARE-MAINTENANCE-OIL is recommended for restorative intensive care. 	

Safety guidance:

The information in this technical data sheet is based on the current knowledge and experience of PLANTAG Coatings GmbH. The product processor is not exempted from its own testing and testing of the products with regard to the intended use as well as the wealth of possible influences during processing and application. Existing laws and regulations are to be observed by the recipient of our products in their own responsibility. Labeling in accordance with the Ordinance on Hazardous Substances and Transport Law can be found in the safety data sheet. A legally binding assurance of certain properties or suitability for a specific purpose cannot be derived from our information. Recommendations deviating from the information in our technical data sheets are only binding for us if they have been confirmed in writing. Our terms and conditions are an integral part of this technical information sheet [Aug-25]

PLANTAG Coatings GmbH
Ohmstraße 8
32758 Detmold
GERMANY
Fon: +49 5231 6002 661
Fax: +49 5231 6002 9661
E-Mail: info@jordanlacke.de

JORDAN LACKE – a trademark of PLANTAG Coatings GmbH