

ARTICLE: JORA-CARE-MAINTENANCE-OIL
ITEM NO.: JW1950-0-001
SYSTEM: CARE-OIL FOR PARQUET

PRODUCT PROPERTIES		SCOPE OF APPLICATION	
<p>Careline are care and cleaning products. They are not only used for the cleaning of your surface, but also for a lasting preservation of value in all areas.</p> <p>JORA-CARE-MAINTENANCE-OIL JW1950-0-001 with short drying time for the first and maintenance care of oiled surfaces is suitable for the regular refreshing of the oil surfaces.</p>		<p>CARE-OIL for initial and maintenance care.</p> <p>Suitable for the care of:</p> <ul style="list-style-type: none"> ▪ Oiled parquet ▪ Oiled furniture 	
TECHNICAL DATA		STORAGE	
<ul style="list-style-type: none"> ▪ Color: transparent ▪ Dosing: 1 liter/ approx. 50-60 m² ▪ Gloss level: matt 		<p>Storage:</p> <p>Store material in a tightly closed container</p> <p>Don't store below 5°C.</p> <p>Shelf-Life:</p> <p>12 months (when stored in the original unopened containers)</p> <p>Use undiluted and do not add water!</p>	
SPECIAL GUIDANCE		APPLICATION	
<ul style="list-style-type: none"> ▪ Shake well before use! ▪ The usual precautions for handling chemicals must be observed. ▪ Do not allow to enter drains or waters. ▪ Keep out of reach of children. Risk of self-ignition with cloth or paper towels wetted with natural oil/furniture oil products (autoxidation)! ▪ Impregnated wipes and cleaning cloths must therefore be dried outdoors or stored in a closed, fireproof container. ▪ Cloths soaked in oil can also be stored covered with water (min. 48 h), after which they can be disposed of with household waste. Keep away from oxygen and light. ▪ Products which dry oxidatively (e.g. oils) and products which form highly flammable residues (e.g. NC lacquers) must not be applied in the same painting booths because of the risk of spontaneous combustion. 		<p>1.) Initial care: (especially for parquet) The surface to be treated must be clean and dry. Apply the care oil pure and in a thin layer. Then massage into the surface using a pad or bale. For parquet we recommend using a single disc machine and a white pad. If necessary, rub/absorb excess with a lint-free cotton cloth. Distribute the care oil until no more traces of the pad, etc. are visible in the wet oil film. Consumption and drying time see "Maintenance care".</p> <p>2.) Maintenance care: The parquet surface to be treated must be clean and dry. The surface can be cleaned e.g. with JORA-CARE-BASIC-CLEANER JZ7920-0-001. Carry out the care regularly with simple cleaning devices (without machines). Apply the care oil pure and as thin as possible. Apply evenly with a cloth or surface wiper and allow to dry for 3-4 hours. The treated surfaces can then be walked on and used gently (depending on room temperature, humidity and ventilation). Please do not walk on the surface during this time! Too frequent use may lead to layer formation. In the living area, depending on the use, carry out approx. every 6 months.</p>	

Safety guidance:

The information in this technical data sheet is based on the current knowledge and experience of PLANTAG Coatings GmbH. The product processor is not exempted from its own testing and testing of the products with regard to the intended use as well as the wealth of possible influences during processing and application. Existing laws and regulations are to be observed by the recipient of our products in their own responsibility. Labeling in accordance with the Ordinance on Hazardous Substances and Transport Law can be found in the safety data sheet. A legally binding assurance of certain properties or suitability for a specific purpose cannot be derived from our information. Recommendations deviating from the information in our technical data sheets are only binding for us if they have been confirmed in writing. Our terms and conditions are an integral part of this technical information sheet [Aug-25]

PLANTAG Coatings GmbH
 Ohmstraße 8
 32758 Detmold
 GERMANY
 Fon: +49 5231 6002 661
 Fax: +49 5231 6002 9661
 E-Mail: info@jordanlacke.de

JORDAN LACKE – a trademark of PLANTAG Coatings GmbH

Item No.: JW1950-0-001