


ARTICLE: AQUA PRO-GRIP
ITEM-NO.: APG 402
SYSTEM: Additive to increase slip resistance

PRODUCT PROPERTIES		SCOPE OF APPLICATION	
<p>AQUA PRO-GRIP APG 402 is a grip additive to increase slip resistance</p> <p>APG 402 is characterised by:</p> <ul style="list-style-type: none"> Improvement of the anti-slip properties 		<p>The product is well suited for:</p> <ul style="list-style-type: none"> lacquers for parquet flooring lacquers for staircase components and steps 	
TECHNICAL DATA		STORAGE	
<ul style="list-style-type: none"> Colour: transparent-white Dosing: 5 L base coat with 1 bottle of AQUA PRO-GRIP APG 402 (corresponds to 2% addition by weight) 		<div>  <p>Store material in a tightly closed container and under dry and cool conditions.</p> </div> <p>Shelf life:</p> <p>APG 402: 36 months</p>	
SPECIAL GUIDANCE		TESTING STANDARDS	
<ul style="list-style-type: none"> Stir AQUA PRO-GRIP APG 402 carefully into the base coat shortly before use. Mixing ratio: 5 L base coat with 1 bottle of AQUA PRO-GRIP APG 402 (corresponds to 2% addition). Process the finished mixture immediately. Keep stirring the material well to avoid an uneven surface texture. Use AQUA PRO-GRIP APG 402 only in the last layer of the coating structure! 		<ul style="list-style-type: none"> Complies with DIN 51130 - Class R 10 in combination with 1C ECO-FINISH EF 55X. 	

Item-No.: APG 402

Safety guidance:

The information in this technical data sheet is based on the current knowledge and experience of PLANTAG Coatings GmbH. The product processor is not exempted from its own testing and testing of the products with regard to the intended use as well as the wealth of possible influences during processing and application. Existing laws and regulations are to be observed by the recipient of our products in their own responsibility. Labeling in accordance with the Ordinance on Hazardous Substances and Transport Law can be found in the safety data sheet. A legally binding assurance of certain properties or suitability for a specific purpose cannot be derived from our information. Recommendations deviating from the information in our technical data sheets are only binding for us if they have been confirmed in writing. Our terms and conditions are an integral part of this technical information sheet [Jun-25]

PLANTAG Coatings GmbH
Ohmstraße 8
32758 Detmold
GERMANY
Fon: +49 5231 6002 661
Fax: +49 5231 6002 9661
E-Mail: info@jordanlacke.de

JORDAN LACKE – a brand of PLANTAG Coatings GmbH