

**ARTICLE:** JORA-CARE-MAINTENANCE-OIL (water-based)  
**TEM-NO.:** JW7955-0-001  
**SYSTEM:** WATER-BASED-CARE-OIL

PRODUCT PROPERTIES		SCOPE OF APPLICATION	
<p>Careline are care and cleaning products. They are not only used for the cleaning of your surface, but also for a lasting preservation of value in all areas.</p> <p>Care oil for initial and maintenance care.</p> <p>JORA-CARE-MAINTENANCE-OIL with short drying time for the initial and maintenance care of oiled surfaces is suitable for the regular refreshing of oiled surfaces</p>		<p>For the care of:</p> <ul style="list-style-type: none"> <li>▪ Oiled parquet</li> <li>▪ Oiled furniture</li> </ul>	
TECHNICAL DATA		STORAGE	
<ul style="list-style-type: none"> <li>▪ Color: colourless</li> <li>▪ Consumption: 1 litre / approx. 40-50 m<sup>2</sup></li> <li>▪ Gloss level: matt</li> </ul>		<p>Store tightly closed in a cool, dry place.</p> <p>Shelf life: 12 months</p> <p>(In tightly closed original containers)</p>	
APPLICATION		SPECIAL GUIDANCE	
<ul style="list-style-type: none"> <li>▪ Use undiluted and do not add to mop water!</li> <li>▪ Initial care: (especially for parquet) The surface to be treated must be clean and dry. Apply the maintenance oil pure and thinly. Then massage into the surface using a pad or massage. For parquet an application with the disc machine and a white pad is recommended. If necessary, rub/absorb excess with a lint-free cotton cloth. Spread the MAINTENANCE-OIL until there are no more traces of the pad, etc. are no longer visible in the wet oil film. Consumption and see 'Maintenance care'.</li> <li>▪ Maintenance care: The parquet surface to be treated must be clean and dry. The surface can be cleaned with JORA-CARE-BASIC-CLEANER JZ7920-0-001, for example. Carry out regularly with simple tools (without machines). Apply the maintenance oil pure and as thinly as possible. Apply evenly with a cloth or surface wiper and leave to dry for 3-4 hours. The treated surfaces are then gently walkable and usable (depending on room temperature, humidity and ventilation). Please do not walk on the surface during this time! Too frequent application can lead to the formation of may occur. In living areas, depending on use, approx. every 6 months.</li> </ul>		<ul style="list-style-type: none"> <li>▪ Shake JORA-CARE-MAINTENANCE-OIL well before use!</li> <li>▪ The usual precautions for handling chemicals precautionary measures must be observed.</li> <li>▪ Keep out of reach of children.</li> <li>▪ Risk of spontaneous combustion with cloths or paper towels wetted with natural oil/furniture oil products (autoxidation)!</li> <li>▪ Soaked application cloths and cleaning cloths must therefore be dry outdoors or in a closed, fireproof container, fireproof container.</li> <li>▪ Rags soaked with oil can also be covered with water (min. 48 h), after which they can be disposed of in the disposed of with household waste. Keep away from oxygen and keep away from light.</li> <li>▪ Products that dry oxidatively (e.g. oils) and products that form highly flammable residues (e.g. NC paints), must not be applied in the same spray booths due to the in the same spray booths due to the risk of spontaneous combustion.</li> </ul>	

## Safety guidance:

The information in this technical data sheet is based on the current knowledge and experience of PLANTAG Coatings GmbH. The product processor is not exempted from its own testing and testing of the products with regard to the intended use as well as the wealth of possible influences during processing and application. Existing laws and regulations are to be observed by the recipient of our products in their own responsibility. Labeling in accordance with the Ordinance on Hazardous Substances and Transport Law can be found in the safety data sheet. A legally binding assurance of certain properties or suitability for a specific purpose cannot be derived from our information. Recommendations deviating from the information in our technical data sheets are only binding for us if they have been confirmed in writing. Our terms and conditions are an integral part of this technical information sheet [Aug-25]

**PLANTAG Coatings GmbH**  
 Ohmstraße 8  
 32758 Detmold  
 GERMANY  
 Fon: +49 5231 6002 661  
 Fax: +49 5231 6002 9661  
 E-Mail: info@jordanlacke.de

JORDAN LACKE – a trademark of PLANTAG Coatings GmbH

Item No.: JW7955-0-001