

ARTICLE: AQUA-CROSSLINKER
ITEM-NO.: JH8413-0-001
SYSTEM: Crosslinker for water-based lacquers to improve adhesion (esp. for glass coating)

TECHNICAL DATA

Crosslinker component for one-component water-based coatings to improve the adhesion properties of the surface (especially on glass). The Aqua-Crosslinker improves the wet and dry adhesion and increases the chemical resistance of the coating.

- Colour: colourless
- Gloss: Not applicable
- Density: approx. 1,166 g/cm³



Store tightly closed in a cool, dry place. Protect from frost and direct sunlight.

Always close containers tightly immediately after removal to prevent the ingress of moisture from the air. Process opened containers as quickly as possible.

Shelf life:

JH8413-0-001: 6 months

(in the unopened original container)

SPECIAL GUIDANCE

- In addition to this technical data sheet, the technical data sheets of the individual products must be observed.
- Depending on the application, an addition of 2 to 5 % is recommended.
- Stir thoroughly immediately after adding to the paint component. 10 minutes waiting time is recommended before starting application.
- After addition, a processing time of approx. 8 hours is recommended, as the positive properties of the crosslinker will then diminish again.

Safety guidance:

The information in this technical data sheet is based on the current knowledge and experience of PLANTAG Coatings GmbH. The product processor is not exempted from its own testing and testing of the products with regard to the intended use as well as the wealth of possible influences during processing and application. Existing laws and regulations are to be observed by the recipient of our products in their own responsibility. Labeling in accordance with the Ordinance on Hazardous Substances and Transport Law can be found in the safety data sheet. A legally binding assurance of certain properties or suitability for a specific purpose cannot be derived from our information. Recommendations deviating from the information in our technical data sheets are only binding for us if they have been confirmed in writing. Our terms and conditions are an integral part of this technical information sheet [Jun-25]

PLANTAG Coatings GmbH

Ohmstraße 8
 32758 Detmold
 DEUTSCHLAND
 Fon: +49 5231 6002 661
 Fax: +49 5231 6002 9661
 E-Mail: info@plantag.de

JORDAN LACKE – a brand of PLANTAG Coatings GmbH