


ARTICLE: CLASSIC-PRO-UV-PROTECT
ITEM-NO.: JA9045-0-001
SYSTEM: Light-Protection-Concentrate

PRODUCT PROPERTIES		SCOPE OF APPLICATION	
CLASSIC-PRO-UV-PROTECT provides extensive protection for fine wood against the harmful effects of UV radiation, thereby counteracting the yellowing of light-coloured woods.		CLASSIC-PRO-UV-PROTECT can be added to all paints in our range with the exception of POLYESTER.	
TECHNICAL DATA		STORAGE	
<ul style="list-style-type: none"> Mixture: 1 litre lacquer + 10 cc CLASSIC-PRO-UV-PROTECT 		<div>  <p>Store material in a tightly closed container and under dry and cool conditions. Shelf life: 12 months (when stored in the original unopened containers)</p> </div>	
PROCESSING		SPECIAL GUIDANCE	
<ul style="list-style-type: none"> CLASSIC-PRO-UV-PROTECT JA9045-0-001 is supplied in liquid form and stirred vigorously into the paint. 		<ul style="list-style-type: none"> It is advisable to add CLASSIC-PRO-UV-PROTECT to the varnish for all light-coloured woods, bleached woods and sensitive stain colours in order to largely counteract yellowing. The best possible protection is achieved when all varnish layers in a multi-layer varnish structure contain CLASSIC-PRO-UV-PROTECT. If this is not possible, CLASSIC-PRO-UV-PROTECT should always be added to the top varnish layer. For two-component paints, the amount to be added must be calculated based on the finished paint mixture (base paint + hardener). 	

Item No.: JA9045-0-001

Safety guidance:

The information in this technical data sheet is based on the current knowledge and experience of PLANTAG Coatings GmbH. The product processor is not exempted from its own testing and testing of the products with regard to the intended use as well as the wealth of possible influences during processing and application. Existing laws and regulations are to be observed by the recipient of our products in their own responsibility. Labeling in accordance with the Ordinance on Hazardous Substances and Transport Law can be found in the safety data sheet. A legally binding assurance of certain properties or suitability for a specific purpose cannot be derived from our information. Recommendations deviating from the information in our technical data sheets are only binding for us if they have been confirmed in writing. Our terms and conditions are an integral part of this technical information sheet [Aug-25]

PLANTAG Coatings GmbH
Ohmstraße 8
32758 Detmold
GERMANY
Fon: +49 5231 6002 661
Fax: +49 5231 6002 9661
E-Mail: info@plantag.de

PLANTAG COATINGS – Competence in lacquer

JORDAN LACKE – eine Marke der PLANTAG Coatings GmbH